

SYSTEM	BRAND	TYPE OF PRODUCT	TECHNICAL SPECIFICATION	SOUND ABSORPTION	RECOMMENDED AREAS
Wall Fixed Acoustic Panels		Live Textile Plank Panel 2DPLP-5480	Live Textile - Plank Panel 2DPLP-5480 This tackable substrate offers moderate acoustical properties. The Live Plank Panel 2DPLP-5480 is constructed with inorganic minerals and fibres making it resistant to moisture and warping. The Plank Panel is a dense material recommended for office areas, passages, and lobbies. It is available in 20mm and 34mm thickness. Maximum Length 1800mm. Fabric Acoustic Panels or Noise Reduction Panels are commonly used in home theatres or home cinemas, recording studios, engineering booths, restaurants, lobbies, bars and cafes, coffee houses, libraries, schools, universities, conference rooms, office buildings, courtrooms, apartment complexes, studio designs, home decor, art galleries, and medical facilities, hospitals or schools for noise reduction.	FREQUENCY TABLE 250Hz - 0.30 315Hz - 0.35 400Hz - 0.39 500Hz - 0.40 630Hz - 0.41 800Hz - 0.42 1000Hz - 0.45 1250Hz - 0.47 1600Hz - 0.50 NRC - 0.46	Architectural Ideal for High Traffic Areas. Homes, Home Cinema Rooms, Offices, Meeting Rooms, Board Rooms Hotels, Community Halls, Restaurants Schools, Auditoriums, Courtrooms, Music studios and rehearsal spaces, auditoriums. Installation The panels are fixed directly to the wall. Installed according to manufacturer's installation guidelines.
			   300mm 450mm 600mm		